

Technical data sheet **NanoGrip**

Product description / Application:

Easy-to-clean, hard-wearing, durable, self-adhesive floor marking tape in conjunction with special acrylate-based adhesive. Suitable for smooth floors in indoor and weather-protected outdoor areas. Anti-slip tape with low abrasion and high tear resistance.

- Durable and tear-resistant
- High abrasion resistance
- Suitable for smooth concrete screed, EP / PU / MMA coatings and tiles

Ideally suited for:

- Hygiene, food and clean room areas
- Marking of hazardous areas
- 5S measure
- Marking of walkways

Technical data:

Optimum bonding temperature: $\geq 12^{\circ}\text{C}$

Area of application: Suitable for industrial purposes

Material: Plastic film

Thickness: 0.3 mm

Slip class: R10 according to DIN EN 16165

Adhesive: Acrylic

Surface: Glossy

Temperature range: 20°C to $+70^{\circ}\text{C}$

Processing instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paints or coatings must be removed or consolidated. After application, the LongLife floor marking should be subjected to pressure for as short a time as possible to increase its durability. Turning and twisting on the tape with industrial trucks or similar heavy vehicles should be avoided and can lead to the destruction of the tape.

Warranty and liability:

Our information and recommendations are based on the current state of knowledge. The values stated in our data sheets