

Technical Data Sheet **ProGrip**

Product Description / Application:

Tape made of PVC carrier material combined with a special acrylic-based adhesive. Suitable for smooth floors indoors and in weather-protected outdoor areas. Coarse-textured anti-slip tape with aluminium oxide grit firmly bonded to a PVC carrier material by means of acrylic resin.

- Withstands intensive foot traffic and light pallet truck traffic
- Durable and tear-resistant
- High abrasion resistance
- Waterproof, chemical-resistant and mineral-oil-resistant
- Can be applied to stairs, ramps, machines, vehicles and much more...

Ideally suited for:

- Marking of stairs, ramps, machines, vehicles and much more...
- Marking of areas with heavy foot traffic
- Marking of hazardous areas

Technical Data:

Optimum bonding temperature: $\geq 12^{\circ}\text{C}$

Field of application: suitable for industrial purposes

Material: PVC

Thickness: 1.5 mm $\pm$ 0.1 mm

Slip resistance class: R13 according to DIN EN 16165

Adhesive: acrylic

Carrier material: PVC with mineral grit embedded in synthetic resin

Temperature range: 15°C to $+70^{\circ}\text{C}$

Processing Instructions: The surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. Turning and manoeuvring on the tape with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the tape.

Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.