

Technical Data Sheet **ESD Floor Marking Tape**

Product Description / Application: The ESD floor marking tape is the professional solution for permanent floor markings in electrostatically sensitive areas. The high-gloss PET-laminated tape offers excellent visibility combined with reliable ESD protection.

- Double-sided ESD protection (adhesive and surface)
- Visual support through ESD logo

Ideally suited for:

- 5S projects
- Floor marking in ESD areas

Technical Data:

Feature	ESD floor marking
Material	Vinyl with PET laminate
Thickness	0.14 mm ± 0.1
Surface resistance	$< 1 \times 10^{10} \Omega$
Resistance to ground	$< 1 \times 10^9 \Omega$
Adhesive	Acrylate adhesive
Available widths	50 mm, 75 mm, 100 mm
Standard length	33 m per roll
Temperature range	-20°C to +70°C
Application temperature	$\geq 12^\circ\text{C}$
Available colors	6 colors
Surface	High-gloss (ESD logo)

Processing Instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. After application, the marking should be subjected to pressure as soon as possible to increase durability. The marking is suitable for smooth industrial floors.

Warranty and Liability: Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.