



Technical Data Sheet **LongLife Heavy Duty** **Tape on roll**

Product Description / Application:

Wear-resistant rigid PVC surface combined with a strongly adhesive modified acrylic.

- For smooth and textured indoor floors
- For smooth concrete screed, EP/PU/MMA coatings, tiles
- Suitable for pedestrian, pallet truck and forklift traffic

Ideally suited for:

- Indoor applications
- Marking of driveways and walkways
- High-traffic areas
- Implementation of 5S measures

Technical Data:

Optimal application temperature: 18 - 25 °C

Area of application: Suitable for industrial use

Material: Rigid PVC

Thickness: 1.3 mm (without liner)

Liner: Silicone paper

Surface: Slightly glossy

Adhesive: Modified acrylic

Adhesive properties: Permanent, extra strong

Temperature range: -20 °C to +70 °C

Processing Instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. For outdoor use, we recommend the Long Life Primer. The tape can be driven over by industrial trucks. Turning and manoeuvring on the tape with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the tape.



Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.