Technical Data Sheet **LongLife Low Duty**

Tape on roll

Product Description / Application:

Soft PVC tape with pressure-sensitive rubber adhesive. It combines good mechanical strength, easy transverse tearing and abrasion resistance with excellent conformability.

- For smooth indoor floors
- Suitable for pedestrian traffic
- For smooth concrete screed, EP/PU/MMA coatings and tiles

Ideally suited for:
- Indoor use
- Temporary marking, e.g. of pilot areas
- Temporary marking of hazardous areas
- Implementation of 5S projects

Technical Data:
Optimal application temperature: ≥ 12 °C
Area of application: For industrial use, temporary marking
Material: Soft PVC
Thickness: 0.16 mm
Surface: Matt
Adhesive: Rubber adhesive
Adhesive properties: Solid adhesion
Temperature range: -20 °C to +120 °C
Tensile strength (CEI EN 60454): ≥ 25 N/cm

Processing Instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. Turning and manoeuvring on the tape with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the tape.

Warranty and Liability:
Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.