

Technical Data Sheet **LongLife Floor Signs**

Product Description / Application:

Ensuring a safe working environment through visual marking of walkways or danger points in accordance with current ASR.

- Suitable for indoor use
- Wear-resistant
- Excellent adhesion to smooth substrates
- Resistance to cleaning machines

Ideally suited for:

- Marking of hazardous areas
- Marking in accordance with current ASR A1.3

Technical Data:

Area of application: Suitable for industrial use

Material: PVC

Adhesive: Modified acrylic

Surface: Textured

Thickness: 0.7 mm

Temperature range: 0 °C to +70 °C

Application temperature: 18 – 25 °C

Processing Instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. The window can be driven over by industrial trucks. Turning and manoeuvring on the window with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the window.

Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time.

As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.