

## Technical Data Sheet **LongLife Clear View**

### Product Description / Application:

Marking of storage and pallet locations with visual colour support. Protects the document thanks to bonding on all 4 sides. Robust PVC for long-lasting use in industrial environments.

- Suitable for indoor use
- Wear-resistant
- Excellent adhesion to smooth substrates
- Resistance to cleaning machines

### Ideally suited for:

- Marking of storage locations
- Implementation of 5S projects

### Technical Data:

Area of application: Suitable for industrial use

Material: PVC

Adhesive: Modified acrylic

Surface: Textured

Thickness: 0.7 mm

Temperature range: 0 °C to +70 °C

Application temperature: 18 – 25 °C

Processing Instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. The window can be driven over by industrial trucks. Turning and manoeuvring on the window with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the window.

### Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values.



Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.