

Technical Data Sheet **LongLife Rough Ground**

Tape on roll

Product Description / Application:

The tape consists of a smooth, fabric-reinforced PU surface and features an extra-permanent synthetic rubber adhesive. It is suitable for indoor use and, thanks to its thick adhesive layer, is also designed for rough/uneven substrates.

Ideally suited for marking:

- rough substrates
- driveways and walkways
- work areas
- danger points
- storage areas

Technical Data:

Optimal application temperature: $\geq 20\text{ °C}$

Area of application: Suitable for industrial use

Material: Polyurethane (fabric-reinforced)

Thickness: 1.1 mm

Surface: Smooth, slightly glossy

Adhesive: Synthetic rubber

Temperature range: -20 °C to $+70\text{ °C}$

Processing Instructions: Surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. For outdoor use, we recommend the Long Life Primer. The tape can be driven over by industrial trucks. Turning and manoeuvring on the tape with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the tape.

Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.