

Technical Data Sheet **Vector**

Product Description / Application:

The demands placed on floor markings in industrial environments are high. Especially in areas with heavy forklift traffic, conventional floor markings are often a weak point, as they peel off or wear out under heavy mechanical stress, particularly from turning forklift movements. Vector solves this problem and offers a durable, resistant alternative.

Ideally suited for:

- Driveways and walkways
- 5S measures
- Storage location marking
- Smooth surfaces/industrial floors
- Indoor areas

Technical Data

Material: polyester

Thickness: 0.2 mm

Surface: glossy

Adhesive: rubber

Application temperature: > 12°C

Short-term temperature resistance: 0°C - 90°C

Processing Instructions: The surfaces must be dry, clean and free of dust, oil, grease and solvents. After application, pressure should be applied to the marking as soon as possible to increase durability. The marking is suitable for smooth industrial floors.

Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.

ORGATEX GmbH

Albert-Einstein-Str. 19
DE-40764 Langenfeld
Tel.: +49 2173 1064-0
info@orgatex.de

Important note:

The information on the properties or usability of materials or products is provided for information purposes only and does not constitute a contractual obligation. The information merely reflects the manufacturers' experience. All information is provided without guarantee. Misprints, errors and changes reserved.