

Technical Data Sheet **LongLife - Photoluminescent**

Product Description / Application:

LongLife Photoluminescent is a hard-wearing, durable, self-adhesive floor marking tape. It is the ideal marking in darkness or heavy smoke. The tape has an extra-high luminance of 200/25 mcd/m² according to DIN 67510 (class C) and is independent of the power supply, maintenance-free and fail-safe.

- Suitable for pedestrians and pallet trucks
- For smooth indoor floors
- Suitable for smooth concrete screed, EP/PU/MMA coatings and tiles

Ideally suited for:

- Marking of escape routes
- Marking of walkways

Technical Data:

Optimal application temperature: $\geq 12\text{ °C}$

Area of application: Suitable for industrial use

Material: PET/PVC

Thickness: 0.6 mm

Luminance: 200/25 mcd/m² according to DIN 67510

Adhesive: Acrylic

Surface: Glossy

Temperature range: 20 °C to +70 °C

Processing Instructions: The surfaces must be dry, clean and free of dust, oil, grease and solvents. Loose paint or coatings must be removed or consolidated. After application, pressure should be applied to the LongLife floor marking as soon as possible to increase durability. Turning and manoeuvring on the tape with industrial trucks or similarly heavy vehicles must be avoided, as this can destroy the tape.

Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values.



Changes and additions are possible at any time. As the use of our products is beyond our control, we accept no liability or warranty whatsoever. We will gladly provide sample material for testing purposes.