

Technical Data Sheet **WALL PROTECTION KIT Type A+**

Warning and protection profiles absorb even the hardest impacts, effectively preventing injuries and material damage. This means that downtime due to injuries and high repair costs are effectively avoided. Thanks to the conspicuous signal colours, sources of danger at edges, projections and obstacles are recognised at an early stage

Profile body	Recyclable polyurethane foam
Surface	Firmly foam-bonded PU film, coloured by reverse printing, hence no external paint layer
Temperature resistance	From -40 °C to 100 °C
Test	Reaction-to-fire test according to DIN EN 13501-1 / class E REACH 1907/2006 (33) & (67) RoHS 2011/65/EU & 2015/863
Colour options	Yellow/black, yellow/black reflective, red/white reflective, daylight fluorescent
Standard length	0.5 m; 1 m
Mounting	Mounting of the Wall Protection Kit is ensured by the supplied fixing material (screws and wall plugs).
Weight	0.5 metre = 0.80 kg 1 metre = 1.6 kg
Shore hardness	Shore A = 40

Subject to technical changes

Warranty and Liability:

Our information and recommendations are based on current knowledge. The values stated in our data sheets are typical or average values. Changes and additions are possible at any time. Since the use of our products is beyond our control, we assume no liability or warranty whatsoever. We are happy to provide you with sample material for testing purposes

Important note:

The information on the properties or usability of materials or products is provided for information purposes only and does not constitute a contractual obligation. The information merely reflects the manufacturers' experience. All information is provided without guarantee. Subject to misprints, errors and changes.

