





Implement forklift-free operations?



Improve the efficiency of an existing tugger train system?



Improve ergonomics and health & safety?



Find a solution to support new production layout?



Move to partial or fully automated operations?





Extremely space-efficient & agile



- ✓ Shorter train and excellent tracking less space required for transportation…save the space for production!
- ✓ Shorter train equals less walking & handling time


Other tugger on the market (ISO) length = 13.200 mm







Loading and unloading from either side







- √ Load/unload from either side
- ✓ No need to U-Turn
- ✓ Create the fastest and most efficient routes through your facility without any worry of sequencing deliveries





Best ergonomics, improve Health & Safety

HEALTH AND SAFETY


- √ Walk-through between mother carts prevented
- ✓ Train doesn't move if carts are not locked
- ✓ Excellent tracking creates a safe work environment
- Smooth rounded corners of the carts a safe work environment



ERGONOMICS

- ✓ Ergonomic handling of up to 1.000 kg per cart!
- ✓ The load tilts toward the operator when unloading.
- ✓ Rooftop shape of the frame for the most ergonomic loading.
- Daughter Cart wheels turn automatically in rolling direction when tilting









Flexible unit for different loads and processes



FLEXIBILITY

- Carries multiple cart sizes without losing train capacity
- ✓ Compatible with all standard tuggers




FIT FOR AUTOMATION

- Compatible with automated tuggers future proof
- √ The LiftLiner can communicate with the AGV tugger
- √ High safety standard for AGV communication (PLd)




Reduced manpower, traffic and number of trains needed, supports standardization











MILKRUN SYSTEM VS FORKLIFT

BENEFIT 1

✓ Less waiting times and less accidents

BENEFIT 2

✓ Fight against labor shortage: LiftLiner can replace 3–6 forklifts and drivers







External width	1000 mm
External length	3200 mm
Tare weight	350 kg
Max load per mother cart	1000 kg
Wheel material	Polyurethane
Wheel size	200 mm
Lifting range	60 mm
Train length with 3 Liftliner®	9600 mm
Maximum train speed	
3 LiftLiner pairs	8 km/h
4 LiftLiner pairs (max length)	6 km/h
U turn radius with 3 Liftliner	4500 mm
Ground clearance	0/60 mm
Maximum slope	10 %
Coupling system	Crossbar system

LiftLiner® is made out of a pair of 2 mother carts. Each mother cart carries a daughter cart or an elephantboard.





	ELEPHANTBOARD®	DAUGHTER CART
External dimensions		
- EURO	1220 x 820 x 1810 mm	1240 x 840 x 318 mm
- ISO		1240 x 840 x 318 mm
Working load capacity	500-1000 kg	1000 kg
Shelf material	Heavy-duty plastic	<u> </u>
Number of shelves	1–6	_
Distance between shelves	228–365 mm	<u> </u>
Tare weight	65 kg	29 kg
Wheel combination	4 swivel	4 swivel
Wheel material	Polyamide	Polyamide
Wheel size	200 mm	200 mm
Surface treatment	-	Blue zinc plated

The LiftLiner® can carry daughter carts sized: 800 x 600 mm 1200 x 1000 mm 1200 x 800 mm









25% more space-efficient compared to other tugger trains

Lifts in 3 seconds and carries 1 tonne per loading position



They are already using LiftLiner®



"We always look for ways to improve our operations. With the LiftLiner® our internal logistics is handled in a more efficient and ergonomic way.

The fact that the LiftLiner® is very compact has also enabled us to reserve more space for our production line."



















IDEAL APPLICATIONS


- + Retail
- + E-commerce
- + Warehousing
- + Manufacturing
- + Automotive
- + Postal & Parcel
- + DIY

K.Hartwall Oy Ab

Kay Hartwallin tie 2 01150 Söderkulla, Finland Tel. +358 9 413 1833 contact-khw@k-hartwall.com www.k-hartwall.com



Watch the video



MAKE THE NEXT SMART MOVE IN LOGISTICS